

Installation Procedure Supplement

Manual 26887 (Revision NEW, 5/2015) SonicFlo™ Gas Fuel Control Valve



See manual 26094 for complete installation, operation, maintenance, and certification information. Publications can be found on our website at www.woodward.com/publications.

Important Definitions



This is the safety alert symbol. It is used to alert you to potential personal injury hazards. Obey all safety messages that follow this symbol to avoid possible injury or death.

- DANGER—Indicates a hazardous situation which, if not avoided, will result in death or serious injury.
- WARNING—Indicates a hazardous situation which, if not avoided, could result in death or serious injury.
- CAUTION—Indicates a hazardous situation which, if not avoided, could result in minor or moderate injury.
- NOTICE—Indicates a hazard that could result in property damage only (including damage to the control).
- IMPORTANT—Designates an operating tip or maintenance suggestion.



The engine, turbine, or other type of prime mover should be equipped with an overspeed shutdown device to protect against runaway or damage to the prime mover with possible personal injury, loss of life, or property damage.

The overspeed shutdown device must be totally independent of the prime mover control system. An overtemperature or overpressure shutdown device may also be needed for safety, as appropriate.



Read this entire manual and all other publications pertaining to the work to be performed before installing, operating, or servicing this equipment. Practice all plant and safety instructions and precautions. Failure to follow instructions can cause personal injury and/or property damage.



This publication may have been revised or updated since this copy was produced. To verify that you have the latest revision, check manual 26455, Customer Publication Cross Reference and Revision Status & Distribution Restrictions, on the publications page of the Woodward website:

www.woodward.com/publications

The latest version of most publications is available on the *publications page*. If your publication is not there, please contact your customer service representative to get the latest copy.



Any unauthorized modifications to or use of this equipment outside its specified mechanical, electrical, or other operating limits may cause personal injury and/or property damage, including damage to the equipment. Any such unauthorized modifications: (i) constitute "misuse" and/or "negligence" within the meaning of the product warranty thereby excluding warranty coverage for any resulting damage, and (ii) invalidate product certifications or listings.

NOTICE

To prevent damage to a control system that uses an alternator or battery-charging device, make sure the charging device is turned off before disconnecting the battery from the system.

NOTICE

To prevent damage to electronic components caused by improper handling, read and observe the precautions in Woodward manual 82715, Guide for Handling and Protection of Electronic Controls, Printed Circuit Boards, and Modules.

Go to www.woodward.com/publications for complete instructions (manual 26094).

Replacement/Exchange: Replacement/Exchange is a premium program designed for the user who is in need of immediate service. It allows you to request and receive a like-new replacement unit in minimum time (usually within 24 hours of the request), providing a suitable unit is available at the time of the request, thereby minimizing costly downtime.

This option allows you to call your Full-Service Distributor in the event of an unexpected outage, or in advance of a scheduled outage, to request a replacement control unit. If the unit is available at the time of the call, it can usually be shipped out within 24 hours. You replace your field control unit with the like-new replacement and return the field unit to the Full-Service Distributor.

Flat Rate Repair: Flat Rate Repair is available for many of the standard mechanical products and some of the electronic products in the field. This program offers you repair service for your products with the advantage of knowing in advance what the cost will be.

Flat Rate Remanufacture: Flat Rate Remanufacture is very similar to the Flat Rate Repair option, with the exception that the unit will be returned to you in "like-new" condition. This option is applicable to mechanical products only.

Returning Equipment for Repair

If a control (or any part of an electronic control) is to be returned for repair, please contact your Full-Service Distributor in advance to obtain Return Authorization and shipping instructions.

When shipping the item(s), attach a tag with the following information:

- return number;
- name and phone number of contact person;
- description of the problem;

- name and location where the control is installed;
- complete Woodward part number(s) and serial number(s);
- instructions describing the desired type of repair.

Contacting Woodward's Support Organization

For the name of your nearest Woodward Full-Service Distributor or service facility, please consult our worldwide directory published at www.woodward.com/directory.

You can also contact the Woodward Customer Service Department at one of the following Woodward facilities to obtain the address and phone number of the nearest facility at which you can obtain information and service.

Products Used In Electrical Power Systems	Products Used In Engine Systems	Products Used In Industrial Turbomachinery Systems
FacilityPhone Number	FacilityPhone Number	FacilityPhone Number
Brazil+55 (19) 3708 4800	Brazil+55 (19) 3708 4800	Brazil+55 (19) 3708 4800
China+86 (512) 6762 6727	China+86 (512) 6762 6727	China+86 (512) 6762 6727
Germany:	Germany +49 (711) 78954-510	India+91 (129) 4097100
Kempen +49 (0) 21 52 14 51	India+91 (129) 4097100	Japan+81 (43) 213-2191
Stuttgart - +49 (711) 78954-510	Japan+81 (43) 213-2191	Korea+82 (51) 636-7080
India+91 (129) 4097100	Korea+82 (51) 636-7080	The Netherlands+31 (23) 5661111
Japan+81 (43) 213-2191	The Netherlands+31 (23) 5661111	Poland+48 12 295 13 00
Korea+82 (51) 636-7080	United States+1 (970) 482-5811	United States+1 (970) 482-5811
Poland+48 12 295 13 00		
United States+1 (970) 482-5811		

Woodward reserves the right to update any portion of this publication at any time. Information provided by Woodward is believed to be correct and reliable. However, no responsibility is assumed by Woodward unless otherwise expressly undertaken.

Copyright © Woodward 2015 All Rights Reserved



PO Box 1519, Fort Collins CO 80522-1519, USA 1000 East Drake Road, Fort Collins CO 80525, USA Phone +1 (970) 482-5811 • Fax +1 (970) 498-3058

Email and Website—www.woodward.com

Regulatory Compliance & Declarations

European Compliance for CE Marking:

These listings are limited only to those units bearing the CE Marking.

EMC Directive: Declared to 2004/108/EC COUNCIL DIRECTIVE of 15 December 2004 on the

approximation of the laws of the Member States relating to electromagnetic compatibility and all applicable amendments. 2004/108/EC is met by evaluation of the physical nature to the EMC protection requirement. Electromagnetically passive or "benign" devices are excluded from the scope of the Directive 2004/108/EC, however they also meet the protection requirement and intent of

the directive.

Pressure Certified to Pressure Equipment Directive 97/23/EC of **Equipment** 29 May 1997 on the approximation of the laws of the

Directive: Member States concerning pressure equipment, Categories II and III, TUV

Rheinland Certificate 01 202 USA/Q-11 6617, Module H

ATEX – Potentially Declared to 94/9/EEC COUNCIL DIRECTIVE of 23

Explosive March 1994 on the approximation of the laws of the **Atmospheres** Member Statesconcerning equipment and protective

Directive: systems intended for use in potentially explosive atmospheres.

Zone 2, Category 3, Group II G, Ex nA IIC T3X Gc, IP54

See below for special conditions for safe use.

Valves with Intrinsically Safe Components Only—

ATEX Potentially
Explosive
Atmospheres

Declared to 94/9/EC COUNCIL DIRECTIVE of 23
March 1994 on the approximation of the laws of the
Member States concerning equipment and protective

Directive: systems intended for use in potentially explosive atmospheres.

Zone 2, Category 3, Group II G, Ex nA IIC T3X Gc, IP54

Special Conditions for Safe Use:

The LVDT and servo valve must be wired using barrier wiring drawings shown in

Figure 1-5.

Servo valve must not be replaced with one that has previously been installed in

'nA' applications.

Other European Compliance:

Compliance with the following European Directives or standards does not qualify this product for application of the CE Marking:

Machinery Compliant as partly completed machinery with Directive

Directive: 2006/42/EC of the European Parliament and the Council of 17 May 2006 on

machinery.

ATEX: Exempt from the non-electrical portion of the ATEX Directive 94/9/EC due to no

potential ignition sources per EN 13463-1.

Other International Compliance

TIIS: Applicable to the servo valve and LVDT. Where customer has requested TIIS

compliance, the servo valve and LVDT are TIIS-marked, and must be installed with

barriers as shown in the wiring diagrams in Chapter 1.

GOST R: Certified for use in explosive atmospheres within the Russian Federation per

GOST R certificate POCC US. МЛ14.В00144 as ExnAIIT3 X.

North American Compliance:

Suitability for use in North American Hazardous Locations is the result of compliance of the individual components:

Servo Valve: FM Certified for Class I, Division 2, Groups A, B, C, D for use in the United

States only per FM 4B9A6.AX.

CSA Certified for Class I, Division 2, Groups A, B, C, D for use in Canada per

CSA 1072373.

Junction Box: UL Listed for Class I, Zone 1: AEx e II, Ex e II, T6 for use in the United States

and Canada per UL E203312.

Dual Coil LVDT: CSA Certified for Class I, Divisions 1 and 2, Groups A, B, C, D, T4 for use in the

United States and Canada per

CSA 151336-1090811.

Triple Coil LVDT: ETL Certified for Class I, Division 2, Groups A, B, C, D, T3 for use in the United

States and Canada per ETL J98036083-003.

Special Conditions for Safe Use—All Valves

Wiring must be in accordance with North American Class I, Division 2, or European Zone 2 Category 3 wiring methods as applicable, and in accordance with the authority having jurisdiction.

Field Wiring must be suitable for at least 100 °C.

The wiring junction box provides earth ground terminals if needed for a separate earth ground to meet wiring requirements.

T3 reflects conditions without process fluid. The surface temperature of this valve approaches the maximum temperature of the applied process media. It is the responsibility of the user to ensure that the external environment contains no hazardous gases capable of ignition in the range of the process media temperatures.

Compliance with the Machinery Directive 2006/42/EC noise measurement and mitigation requirements is the responsibility of the manufacturer of the machinery into which this product is incorporated.

The risk of electrostatic discharge is reduced by permanent installation of the valve, proper connection to the protective earth (PE) terminals, and care when cleaning. The valve should not be cleaned unless the area is known to be non-hazardous.



EXPLOSION HAZARD—Do not connect or disconnect while circuit is live unless area is known to be non-hazardous.

Substitution of components may impair suitability for Class I, Division 2 or Zone 2 applications.



RISQUE D'EXPLOSION—Ne pas raccorder ni débrancher tant que l'installation est sous tension, sauf en cas l'ambiance est décidément non dangereuse.

La substitution de composants peut rendre ce matériel inacceptable pour les emplacements de Classe I, applications Division 2 ou Zone 2.

DECLARATION OF CONFORMITY

Manufacturer's Name: WOODWARD, INC. Manufacturer's Address: 1000 E. Drake Rd.

Fort Collins, CO, USA, 80525

Sonic FloTM Gas Fuel Control Valves Model Name(s)/Number(s):

Sizes 2", 3", 4" and 6", Classes 300 and 600, Size 8" Class 300

Conformance to Directive(s):

97/23/EC COUNCIL DIRECTIVE of 29 May 1997 on the approximation of the laws of the Member States concerning Pressure Equipment, Category II and III

94/9/EC COUNCIL DIRECTIVE of 23 March 1994 on the approximation of the laws of the Member States concerning equipment and protective systems intended for use in

potentially explosive atmospheres.

2004/108/EC COUNCIL DIRECTIVE of 15 December 2004 on the approximation of the laws of the Member States relating to electromagnetic compatibility and all applicable amendments. 2004/108/EC is met by evaluation of the physical nature to the EMC protection requirement. Electromagnetically passive or "benign" devices are excluded from the scope of the Directive 2004/108/EC, however, they also meet the

protection requirement and intent of the directive.

Marking(s):

(E) Category 3, Group II G, Ex nA IIC T3X Gc, IP54

Applicable Standards:

ASME B31.3 Process Piping, Ed. 08

ASME Boiler and Pressure Vessel Code VIII, Div. 1, Ed. 2007-A08 ASME Boiler and Pressure Vessel Code VIII, Div. 2, Ed. 2010

EN 60079-0 :2012 - Explosive atmospheres - Part 0 : Equipment - General

Requirements

EN 60079-15:2010 - Explosive atmospheres - Part 15: Equipment protection by type

of protection n

EN 61000-6-4, 2007: EMC Part 6-4: Generic Standards - Emissions for Industrial

Environments. (By technical evaluation, not testing.)

EN 61000-6-2, 2005: EMC Part 6-2: Generic Standards - Immunity for Industrial

Environments. (By technical evaluation, not testing.)

Conformity Assessment: PED Module H – Full Quality Assurance, Certificate: 01 202 USA/Q-11 6617

Notified Body

TÜV Rheinland Industrie Service GmbH (ID-No. 0035)

For Pressure Equipment:

Am Grauen Stein, D-51105 Köln

Germany

We, the undersigned, hereby declare that the equipment specified above conforms to the above Directive(s).

MANUFACTURER

Signature

Christopher Perkins

Full Name

Engineering Manager

Position

Woodward, Inc., Fort Collins, CO, USA

Place

Date

5-09-1183 Rev 16, 22-Jan-2009

00145-04-CE-02-03

DECLARATION OF INCORPORATION Of Partly Completed Machinery 2006/42/EC

Manufacturer's Name: WOODWARD, INC.

Manufacturer's Address: 1000 E. Drake Rd. 3800 N. Wilson Ave.

Fort Collins, CO, USA, 80525 Loveland, CO, USA 80538

Model Names: Sonic FloTM Gas Fuel Control Valves

Sizes 2", 3", 4" and 6", Class 300 and 600, Size 8" Class 300

This product complies, where applicable, with the following

Essential Requirements of Annex I: 1.1, 1.2, 1.3, 1.4, 1.5, 1.6, 1.7

The relevant technical documentation is compiled in accordance with part B of Annex VII. Woodward shall transmit relevant information if required by a reasoned request by the national authorities. The method of transmittal shall be agreed upon by the applicable parties.

The person authorized to compile the technical documentation:

Name: Ralf Friedrich, Group Director, Quality, EPS

Address: Woodward GmbH, Handwerkstraße 29, 70565 Stuttgart, Germany

This product must not be put into service until the final machinery into which it is to be incorporated has been declared in conformity with the provisions of this Directive, where appropriate.

The undersigned hereby declares, on behalf of Woodward Governor Company of Loveland and Fort Collins, Colorado that the above referenced product is in conformity with Directive 2006/42/EC as partly completed machinery:

Signature
Suhail Horan

Full Name

Quality Manager

Position

Woodward, Inc., Fort Collins, CO, USA

Place

Date

5-09-1182 (REV. 11) 00145-04-CE-02-01